HIAKA ONE DEPARTURE (RNAV)

(HIAKA1.HIAKA) 20JUN19

KAHULUI (OGG)(PHOG)

KAHULUI, HAWAII

TOP ALTITUDE: 16000

NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: GPS required.
NOTE: Turbojet and turboprop aircraft only.
NOTE: APACK departures expect direct/vectors to APACK/R463.
NOTE: CANON departures expect direct/vectors to CANON.
NOTE: CARRP departures expect direct/vectors to CARRP/A579.
NOTE: CHOKO departures expect direct/vectors to CHOKO.
NOTE: CLUTS departures expect direct/vectors to CLUTS/R465.
NOTE: DANNO departures expect direct/vectors to DANNO.
NOTE: DOVRR departures expect direct/vectors to DOVRR/B596.
NOTE: EBBER departures expect direct/vectors to EBBER/R577.
NOTE: JULLE departures expect direct/vectors to JULLE.
NOTE: KOA departures expect direct/vectors to KOA VORTAC.
NOTE: LILIA departures expect direct/vectors to LILIA.
NOTE: NONNI departures expect direct/vectors to NONNI.
NOTE: PUPPI departures expect direct/vectors to PUPPI
NOTE: SAKKI departures expect direct/vectors to SAKKI.
NOTE: SCOON departures expect direct/vectors to SCOON.

ATIS 128.6
CLNC DEL 120.6 290.5
GND CON 121.9 279.6
MAUI TOWER★ 118.7 279.6
HCF APPROACH
NORTH 120.2 322.4
SOUTH 119.5 225.4

ZIGIE
APACK
THOMA
DANNO
CLUTS
CANON
LILIA
SYVAD
PUPPI
ROSAH
1600
024°
024° (2)
EBBER
HIAKA
554
NONNI
JULLE
SAKKI
N
CHOKO
SCOON
UPOLU POINT
UPP
KONA
KOA
CARRP
DOVRR
TARDE

TAKEOFF MINIMUMS

Rwy 2: Standard with minimum climb of 500′ per NM to 554.
Rwys 5, 20, 23: NA - ATC.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb heading 024° to 554, then direct HIAKA, thence. . . .

. . . .on track 024° to cross ROSAH at or above 1600, then on track 024° for RADAR vectors to assigned route/fix, maintain 16000 or as assigned by ATC. Expect clearance to filed altitude/flight level within 10 minutes after departure.

(HIAKA1.HIAKA) 20030

AL-762 (FAA)

KAHULUI (OGG)(PHOG)

KAHULUI, HAWAII