ILS or LOC RWY 24

NORTHEAST ALABAMA RGNL (GAD)

LOC/DME I-GAD	APP CRS	Rwy Idg	6802
108.35	244°	TDZE	560
Chan 20 (Y)		Apt Elev	569

▼ DME required. VDP NA when using Anniston altimeter setting. When local altimeter setting not received, use Anniston altimeter setting and increase DA to 845 feet and all visibilities ¼ SM: increase all MDAs 80 feet and visibility S-LOC Cats C and D ¼ SM and Circling Cat C ½ SM.

MISSED APPROACH: Climb to 3600 on GAD VOR/DME R-231 to STAMP/GAD 10 DME and hold, continue climb-in-hold to 3600.

AWOS-3PT	BIRMINGHAM APP CON	CLNC DEL	UNICOM
127.825	125.45 279.65	120.05 257.7	122.8 (CTAF) L

ALTERNATE MISSED APCH FIX

114.4 VUZ Chan 91 — 067° — 247° — R-067 — STAMP VUZ 35.1

DME REQUIRED

(IAF) EBAZE GAD 23.1

3600 NoPT to HUBJU 184° hdg (8.7) and 244° (4.4)

GAD R-059

1949 1399

(IF/IAF) HUBJU I-GAD 14.4

064° — 1 min — 244° — (CFRZN)

FIKOX I-GAD 10.2

1277

3600 to HUBJU 059° (13.1)

WANEB I-GAD 4.6

991 991 1196 1280

GADSDEN 112.3 GAD Chan 70

2500 — 244° — 3000 — (4.2) — (2.9) — LR-069

GAD 13.1 Arc — 3600 NoPT

MSA GAD 25 NM — 3400

1208 735 825 804

BLKEY I-GAD 7.3

1757

R-089

(IAF) MAYES GAD 13.1

710 1135 1495 1316

1749

R-231 — 051° — 231°

STAMP GAD 10

LOCALIZER 108.35 I-GAD Chan 20(Y)

ELEV 569 | TDZE 560

244° 6 NM from FAF

8L — 4806 X 100 — 6802 X 150 — 0.3% UP — 36 — 603

3600 | GAD R-231 | STAMP

Use I-GAD DME when on the localizer course.

*LOC only.

HUBJU I-GAD 14.4 — FIKOX I-GAD 10.2 — BLKEY I-GAD 7.3 — WANEB I-GAD 4.6 — 2500 — *I-GAD 3 — I-GAD 1.3

One Minute Holding Pattern

064° → 3600 — 244° ← 244° — 3000

1620* — 2500

GS 3.00° TCH 43

1.7 NM — 1.6 NM — 2.7 NM — 2.9 NM — 4.2 NM

CATEGORY	A	B	C	D
S-ILS 24	779-¾ 219 (300-¾)			
S-LOC 24	1140-1 580 (600-1)		1140-1¾ 580 (600-1¾)	
C CIRCLING	1140-1 571 (600-1)		1440-2½ 871 (900-2½)	1680-3 1111 (1200-3)

HIRL Rwy 6-24 L
MIRL Rwy 18-36 L
REIL Rwys 6 and 24 L

SE-4, 15 MAY 2025 to 12 JUN 2025
SE-4, 15 MAY 2025 to 12 JUN 2025