

COPTER ILS or LOC RWY 10R

FLYING CLOUD (FCM)


LOC FFCM 109.7	APP CRS 098°	Rwy Idg TDZE Apt Elev	5001 906 906
--------------------------	------------------------	-----------------------------	---

⚠ For inoperative MALSR, increase visibility to 1/2 mile. When local altimeter setting not received, use Minneapolis-St Paul Intl-Wold Chamberlain altimeter setting and increase DA 34 feet and all MDA 40 feet.

MALSR

MISSED APPROACH: Climb to 1600 then climbing right turn to 2600 direct FCM
VOR/DME and hold, continue climb-in-hold to 2600.



ATIS 124.9	MINNEAPOLIS APP CON 134.7 284.7	FLYING CLOUD TOWER * 119.15 (CTAF)	GND CON 121.7	CLNC DEL 121.7 (When twr closed)	UNICOM 122.95
----------------------	---	---	-------------------------	---	-------------------------



NC-1, 15 MAY 2025 to 12 JUN 2025

NC-1, 15 MAY 2025 to 12 JUN 2025

ELEV 906	TDZE 906
----------	----------



CATEGORY	COPTER				
H-ILS 10R	1106-1/4	200 (200-1/4)			
H-LOC 10R	1400-1/4	494 (500-1/4)			
GOBKKE FIX MINIMUMS (DME REQUIRED)					
H-LOC 10R	1280-1/4	374 (400-1/4)			
HIRL Rwy 10R-28L					
REIL Rwy 10L and 28R					
REIL Rwy 18, 28L, and 36					
MIRL Rwy 10L-28R					
MIRL Rwy 18-36					
FAF to MAP 5.2 NM					
Knots	45	60	75	90	105
Min:Sec	6:56	5:12	4:10	3:28	2:58