

WAAS CH 73032 W10A	APP CRS 099°	Rwy Idg TDZE 1179 Apt Elev 1182
--	------------------------	---

RNAV (GPS) RWY 10

MOUNTAIN VIEW (MNF)


RNP APCH - GPS.

▼ Procedure NA at night. Rwy 10 helicopter visibility reduction below 1 SM


▲ NA NA. Use West Plains altimeter setting, when not received, use Fort Leonard Wood altimeter setting and increase all MDA 80 feet; increase LP Cats C and D visibility ¼ mile, increase LNAV Cat B visibility ¼ mile, LNAV Cats C and D visibility ⅓ mile, and increase Circling Cats B and C visibility ¼ mile.

MISSED APPROACH: Climb to 3700 direct TIYUR and hold.

UNO ASOS 123.825	KANSAS CITY CENTER 128.35 284.675	UNICOM 122.8 (CTAF)
----------------------------	---	-------------------------------



ELEV 1182	TDZE 1179
-----------	-----------



		Visual Segment - Obstacles.			
		3700	TIYUR		
		4 NM Holding Pattern	ZOLAK	YIGPU	CUNIM 3.1 NM to RW10
		3700	2800	2200	RW10
		6 NM		1.9 NM	3.1 NM
CATEGORY		A	B	C	D
LP	MDA	1780-1	601 (600-1)	1780-1¾	601 (600-1¾)
LNAV	MDA	1820-1	641 (700-1)	1820-1⅞	641 (700-1⅞)
CIRCLING		1880-1 698 (700-1)	2080-1¼ 898 (900-1¼)	2080-2¾ 898 (900-2¾)	2180-3 998 (1000-3)