

(DAWNN1.DAWNN) 23334  
**DAWNN ONE DEPARTURE**


AL-6452 (FAA)

INDIANAPOLIS RGNL (MQJ)  
 INDIANAPOLIS, INDIANA

**TOP ALTITUDE:  
 ASSIGNED BY ATC**

AWOS-3PT  
 124.175  
 CLNC DEL  
 119.25  
 INDIANAPOLIS DEP CON  
 127.15 317.8

BRICKYARD  
 116.3 VHP  
 Chan 110



R-098  
 TERRE HAUTE  
 115.3 TTH  
 Chan 100


R-174  
 (28)  
 SNEVA  
 RADAR

TAKEOFF MINIMUMS:

Rwys 7, 16, 25: Standard.  
 Rwy 34: 300-1 or standard with minimum climb  
 of 347' per NM to 1100.

R-113  
 HOOSIER  
 110.2 OOM  
 Chan 39

(47)  
 FOYTT  
 RADAR



6000  
 174°  
 (75)  
 DAWNN  
 10000  
 (For LOUISVILLE Transition)

6000  
 \*2300  
 182°  
 (40)  
 R-002

10000  
 \*3000  
 131°  
 (41)  
 R-311

LOUISVILLE  
 114.8 IU  
 Chan 95

MYSTIC  
 108.2 MYS

- NOTE: RADAR required.
- NOTE: Select appropriate localizer/DME frequency/channel prior to departure.
- NOTE: Turbojets accelerate to 250K until reaching 10000, if unable advise ATC.
- NOTE: Assigned to aircraft with a requested altitude of 11000 or above.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

EC-2, 15 MAY 2025 to 12 JUN 2025

EC-2, 15 MAY 2025 to 12 JUN 2025